


Q-CEILING



Ceiling mount series. Fixtures consist of:


- Multi-step powder-coat painting process, optimized against UV rays and corrosion.
- Copper-free extruded aluminum housing and copper-free precision die-cast aluminum ring/faceplate, bracket and mounting plate.
- Extra-clear, tempered, silk-screened, flat glass diffuser.
- Custom molded, anti-aging gasket(s).
- Stainless steel external hardware.
- High-efficiency COB, combined with an optimized passive cooling system, provides a long LED life.
- Internal specular reflector coated with 5-layers of PVD 99.98% pure aluminum providing >95% reflection.
- Circular Intensive beam angle (C/I).
- Marine Grade finish .
- Suitable for Natatorium applications.

- Circular Medium beam angle (C/M).
- Diffuse light emission (SOFT).
- Input voltage: 120-277 V (50 / 60 Hz), integral 0-10 V dimming driver.
- Five optional finishes available. Add finish suffix to any part number for textured Black (BK-81), Iron gray (AN-96), Aluminum metallic (GR-94), White (WH-87), Iron rust (RB-10) when not standard.
- Consult factory for dimming options, marine-grade, custom finishes (please specify RAL color), and non-cataloged CCT (Kelvin) options including static colors.
- Product meets Buy American Act requirements within ARRA.
- 5-year warranty.
- IDA DARK SKY Approved - 3000K and below



FINISHES

- AN-96 / Iron gray / Textured
- GR-94 / Aluminum metallic / Textured
- WH-87 / White / Textured
- BK-81 / Black / Textured
- RB-10 / Iron rust / Textured



Q
CEILING

Lumen Output 30W	27K	3K	35K	4K	5K
Q-Ceiling 20°	2784	2876	2968	3061	3153
Q-Ceiling 40°	2769	2861	2953	3045	3137
Q-Ceiling 85°	2804	2897	2990	3084	3177
Q-Ceiling Soft	2190	2270	2350	2430	2510

Scan here
for installation
instructions



Order Guide - Q-CEILING




Order code example

QCE-30W-C/I-IG-3K-277-ELV

QCE-

Wattage	Optics	Finish	Kelvin	Voltage	Controls	Accessories
16W 16 watt (AMB Max)	C/I 20° Beam	AM Aluminum Metallic	27K 2700k	UNV 120-277V	NA Non Dimming	CON2 (double-gang j-box, adaptor plate and 1/2" knockouts)
18W 18 watt	C/M 40° Beam	IG Iron Gray	3K 3000k		0-10V 0-10V Dimming	
20W 20 watt	C/EW 85° Beam	IR Iron Rust	35K 3500k		ELV ELV Dimming	CON4 (double-gangj-box, adaptor plate and 3/4" knockouts)
30W 30 watt (max)	SOFT Diffused light	BK Textured Black	4K 4000k			REM Remote mounted Emergency battery back-up
XX Specify wattage must be under max		WH Textured White	5K 5000K			
		CC Custom Color	RED Red			
			BLU Blue			
			GRN Green			
			AMB Amber (16W max)			
			RGBW* RGBW			
			*See below for control details			



CON

**Surface Mounted
J-box with Conduit Entry**

Performance in Lighting reserves the right to make all necessary changes without prior notice.

Performance in Lighting - 2621 Keys Pointe - Conyers, Georgia 30013 - USA - voice 770.822.2115 - info.usa@pil.lighting
www.performanceinlighting.com

Revision 08
03/24

RGBW ACCESSORIES

Power Supply



17433
Kit driver 48V



17096
Kit driver 48V WP


RF Controls



3104173
RGBW RF controller 4 channel
(0.35A each CH)



31041730
RGBW RF controller WP 4 channel
(0.35A each CH)



310429
RGBW hand held remote

DMX Controls



178973
RGBW DMX enabler/decoder 4
channel (0.35A each CH)



1789730
RGBW DMX enabler/decoder WP 4
channel (0.35A each CH)