



# INSERT+2



- Recessed wall steplight series. Fixtures consist of:
- Multi-step powder-coat painting process, optimized against UV rays and corrosion.
  - Copper-free precision die-cast aluminum housing and ring/faceplate.
  - Frosted, flat, tempered silk-screened soda-lime glass diffuser.
  - Custom molded, anti-aging gasket(s).
  - Stainless steel external hardware.
  - Custom MCPCB utilized to maximize heat dissipation and promote a long LED life.
  - IESNA Type III light distribution.
  - Input voltage: 120-277 V (50 / 60 Hz), integral driver.
- Pre-wired factory sealed cable for external electrical connection included.
  - Consult factory for dimming options, custom finishes (please specify RAL color), and non-cataloged CCT (Kelvin) options.
  - Consult factory for custom pre-wired factory sealed cable length options.
  - Stainless steel recessed rough-in kit to be ordered separately.
  - Product meets Buy American Act requirements within ARRA.
  - 5-year warranty.
  - Marine Grade finish.
  - Suitable for Natatorium applications.



- FINISHES**
- AN-96 / Iron gray / Textured
  - GR-94 / Aluminum metallic / Textured
  - WH-87 / White / Textured
  - BK-81 / Black / Textured
  - RB-10 / Iron rust / Textured



INSERT+  
2

Lumen Output	27K	3K	35K	4K	5K	6K
Insert+2	481	503	528	553	578	603

11W Max Wattage

Scan here  
for installation  
instructions



# Order Guide - Insert+2




Order code example

**IN+2**


Wattage	Finish	Kelvin	Voltage	Controls	Accessories
<b>8</b> 8 watt	<b>AM</b> Aluminum Metallic	<b>27K</b> 2700k	<b>UNV</b> 120-277V	<b>NA</b> Non Dimming	<b>ADP</b> Retrofit adaptor plate
<b>11</b> 11 watt (max)	<b>IG</b> Iron Gray	<b>3K</b> 3000k		<b>ELV</b> ELV Dimming	<b>TP</b> Tamper Proof hardware
<b>XX</b> Specify Wattage Must be below max	<b>IR</b> Iron Rust	<b>35K</b> 3500k			
	<b>BK</b> Textured Black	<b>4K</b> 4000k			
	<b>WH</b> Textured White	<b>5K</b> 5000k			
	<b>CC</b> Custom Color	<b>AMB</b> Static Amber Turtle Friendly (590nm)			
		<b>RED</b> Static Red			
		<b>BLU</b> Static Blue			
		<b>GRN</b> Static Green			
		<b>RGBW*</b> RGBW See below for control details			

## ACCESSORIES

### INSERT+



Standard Rough-In  
Included with Fixture  
310486  
**ROUGH-IN**



Retrofit Adapter  
Plate  
ADP  
Goof Ring  
Contact Factory for  
Custom Adapter Plates/  
Goof Rings

## REMOTE RGBW ACCESSORIES

### Power Supply



**17433**  
Kit driver 48V



**17096**  
Kit driver 48V WP


### RF Controls



**3104173**  
RGBW RF controller 4 channel  
(0.35A each CH)



**31041730**  
RGBW RF controller WP 4 channel  
(0.35A each CH)



**310429**  
RGBW hand held remote

### DMX Controls



**178973**  
RGBW DMX enabler/decoder 4  
channel (0.35A each CH)



**1789730**  
RGBW DMX enabler/decoder WP 4  
channel (0.35A each CH)



**11015**  
Terminating Resistor



**110150**  
Terminating Resistor WP