

CRICKET+ 10



In-ground series. Fixtures consist of:

- Copper-free die-cast corrosion-resistant aluminum housing and trim.
- Copper-free die-cast corrosion-resistant aluminum housing.
- AISI 316 stainless steel trim.
- Extra-clear, tempered, silk-screened, flat glass diffuser.
- Frosted, tempered, silk-screened, flat glass diffuser (C/EW versions).
- Custom molded, anti-aging gasket(s).
- Stainless steel external hardware.
- Custom MCPCB utilized to maximize heat dissipation and promote long LED life.
- High-transmittance transparent optics.
- Circular Intensive beam angle (C/I).
- Circular Medium beam angle (C/M).
- Diffuse light emission (C/EW).
- Input voltage: 120-277 V (50 / 60 Hz), integral driver.
- Pre-wired factory sealed cable for external electrical connection included.

- Each rough-in kit is provided with a protective faceplate to avoid possible deformations during the installation in concrete to simplify installation.
- Thermoplastic compression-molded rough-in kit can be ordered separately.
- For outdoor inground applications, provide drainage gravel at least 12" below the rough-in or a suitable drainage system.
- Frosted (FRST) and Non-Slip (NS) glass option available - add suffix to any part number.
- Consult factory for additional optic options.
- Consult factory for dimming options, marine-grade, custom finishes (please specify RAL color), and non-cataloged CCT (Kelvin) options including static colors.
- Product meets Buy American Act requirements within ARRA.
- 5-year warranty.
- Marine Grade finish.
- Suitable for Natatorium applications.




FINISHES

- AN-96 / Iron gray / Textured
- INOX / Stainless steel / Matt
- BK-81 / Black / Textured
- GR-94 / Aluminum metallic / Textured
- WH-87 / White / Textured
- RB-10 / Iron rust / Textured

| Lumen Output | 27K | 3K | 35K | 4K | 5K |
|-----------------|-----|-----|-----|-----|-----|
| Cricket+10 C/EW | 127 | 132 | 137 | 142 | 147 |
| Cricket+10 C/I | 400 | 415 | 430 | 446 | 461 |
| Cricket+10 C/M | 391 | 406 | 421 | 436 | 451 |

6W Max Wattage



CRICKET+
10



Scan here
for installation
instructions

FIXTURES INCLUDE 120-277V 50/60HZ INTEGRAL DRIVERS UNLESS OTHERWISE NOTED

Order Guide - Cricket+



Order code example


C+-10-6-C/I-AM-3K-NA-FRST

C+

| Housing Style | Wattage | Optics | Finish | Kelvin | Voltage | Controls | Options |
|-------------------------|---|---|---|---|---|--|--|
| 10 Cricket+10 | 3.5 3.5 watt RGBW/TW Remote Only 6 6 watt Cricket (Max) XX Specify wattage must be below max | C/I 8° C/M 30° C/EW 88° | AM Aluminum Metallic IG Iron Gray IR Iron Rust BK Textured Black WH Textured White BRS Brass INOX Stainless Steel CC Custom Color | 27K 2700K 3K 3000k 35K 3500K 4K 4000k AMB Static Amber RED Static Red RGBW* (3.5W) TW* Tunable White (3.5W) *See below for control details | UNV 120-277V not suitable for RGBW or TW | NA Non Dimming 0-10V 0-10V Dimming Remote only +10 | RDR Remote Driver FRST Frosted Glass NS Non-Slip Glass LVR Hex Louver |


INCLUDED ACCESSORIES

| DESCRIPTION | FINISH | PART NUMBER |
|-------------------------------|--------|----------------|
| CRICKET+ 10 | | |
| Recessed fixing kit | | 3109879 |
| Recessed fixing kit - RGBW/TW | | 3113571 |



3109879

Rough-in Kit CRICKET+ 10 RGBW/TW



3113571

OPTIONAL RGBW ACCESSORIES

| DESCRIPTION | FINISH | PART NUMBER |
|-----------------------------|--------|--------------|
| Controls | | |
| Kit driver 48V | | 17433 |
| Kit driver 48V Wet Location | | 17096 |



Product is supplied with integral DMX controllers, and remote 48VDC power supply. Controls by others.

TECHNICAL DATA

CRICKET+10

